



SAFETY DATA SHEET STYCCOBOND F60

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STYCCOBOND F60

Internal identification SBF60/20

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Flooring Adhesive

Uses advised against None

1.3. Details of the supplier of the safety data sheet

Supplier

F.Ball and Co. Ltd.
Churnetside Business Park,
Station Road,
Cheddleton,
Leek,
Staffordshire. ST13 7RS
Tel: 01538 361633 Mon-Fri 8.30am-5.00pm (Exc Bank Holidays)
Fax: 01538 361622
E.mail: msds@f-ball.co.uk

1.4. Emergency telephone number

Emergency telephone 01538 361633 Mon-Fri 8.30am - 5.00pm (excluding Bank Holidays)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373

Environmental hazards Aquatic Chronic 2 - H411


Human health Contains a substance with possible risk of harm to the unborn child.

Environmental Toxic to aquatic life with long lasting effects.

Physicochemical The product is highly flammable.

2.2. Label elements

Pictogram



STYCCOBOND F60

Signal word	Danger
Hazard statements	H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe vapour/ spray. P273 Avoid release to the environment. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P313 Get medical advice/ attention.
Contains	TOLUENE, NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN, ACETONE, BUTANONE
Supplementary precautionary statements	P243 Take precautionary measures against static discharge. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN		30-60%
CAS number: 64742-49-0		EC number: 265-151-9
Classification Flam. Liq. 1 - H224 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411		

STYCCOBOND F60

TOLUENE	30-60%
CAS number: 108-88-3	EC number: 203-625-9
Classification Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 Repr. 2 - H361d STOT SE 3 - H336 STOT RE 2 - H373 Asp. Tox. 1 - H304	
ACETONE	1-10%
CAS number: 67-64-1	EC number: 200-662-2
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	
BUTANONE	1-10%
CAS number: 78-93-3	EC number: 201-159-0
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	

The full text for all hazard statements is displayed in Section 16.

Composition comments A solution of resins and elastomers in a blend of organic solvents.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Remove affected person from source of contamination.
Inhalation	Move affected person to fresh air at once. Get medical attention.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea. May cause an asthma-like shortness of breath. May cause damage to organs through prolonged or repeated exposure.
Ingestion	May cause discomfort if swallowed.

STYCCOBOND F60

Skin contact	Skin irritation. May cause an allergic skin reaction.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	In case of fire toxic gases/vapours may be formed. The product is highly flammable.
Hazardous combustion products	Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting	Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate non-essential personnel from the spill area. No smoking, sparks, flames or other sources of ignition near spillage. Take precautionary measures against static discharge and arcing from electrical equipment. Avoid inhalation of vapours and contact with skin and eyes. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Provide adequate ventilation. Use suitable respiratory protection if ventilation is inadequate.
-----------------------------	--

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Contain and absorb spillage with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal as hazardous waste.
--------------------------------	--

6.4. Reference to other sections

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.
------------------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

STYCCOBOND F60

Usage precautions

Observe any occupational exposure limits for the product or ingredients. Avoid inhalation of vapours and spray/mists. Vapours may accumulate on the floor and in low-lying areas. Do not use in confined spaces without adequate ventilation and/or respirator. Eliminate all sources of ignition. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Stored in tightly closed original container in a cool, dry well ventilated place at a temperature between 5 deg C and 30 deg C. Protect against physical damage and/or friction. Keep away from heat, static or electrical sparks, open flame and direct sunlight. Avoid contact with oxidising agents. Keep separate from food, feedstuffs, fertilisers and other sensitive material.

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

TOLUENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 191 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 384 mg/m³

Sk

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm 600 mg/m³

Short-term exposure limit (15-minute): WEL 300 ppm 899 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Sk = Can be absorbed through skin.

ACETONE (CAS: 67-64-1)

DNEL

Industry - Dermal; Short term systemic effects: 186 mg/m³

Industry - Inhalation; Long term systemic effects: 1210 mg/m³

Industry - Inhalation; Short term local effects: 2420 mg/m³

Consumer - Dermal; Long term systemic effects: 62 mg/kg/day

Consumer - Inhalation; Long term systemic effects: 200 mg/m³

Consumer - Oral; Long term systemic effects: 62 mg/m³

PNEC

- Fresh water; 10.6 mg/l

- Marine water; 1.06 mg/l

- Sediment (Freshwater); 30.4 mg/kg

- Sediment (Marinewater); 3.04 mg/kg

- Soil; 29.5 mg/kg

- STP; 100 mg/l

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. Use explosion-proof general and local exhaust ventilation.

STYCCOBOND F60

Personal protection	Always check applicability with your supplier of protective equipment.
Eye/face protection	If there is a risk of splashing, wear chemical resistant goggles or visor approved to BS EN166.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Nitrile gloves to BSEN374 are recommended. Break through times can vary depending on thickness, use and source. Change gloves regularly.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Hygiene measures	Provide eyewash station. Remove contaminated clothing and wash the skin thoroughly with soap and water after work. Do not smoke in work area. Good personal hygiene practices should be followed when working with chemicals.
Respiratory protection	In case of inadequate ventilation use a respirator suitable for organic vapours. Consult respirator manufacturer for specific advice.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Viscous liquid.
Colour	Brown.
Odour	Organic solvents.
Odour threshold	Not determined.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	Not determined.
Flash point	1°C
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not determined.
Upper/lower flammability or explosive limits	Not determined.
Other flammability	Not determined.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.85-0.89 approx @ 20°C
Bulk density	Not determined.
Solubility(ies)	Insoluble in water.
Partition coefficient	Not determined.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.

STYCCOBOND F60

Viscosity	Viscous
Explosive properties	Not determined.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not determined.
Comments	Information given is applicable to the product in its ready-to-use form.

9.2. Other information

Other information	None.
Refractive index	Not determined.
Particle size	Not applicable.
Molecular weight	Not determined.
Volatility	Not determined.
Saturation concentration	Not applicable.
Critical temperature	Not determined.
Volatile organic compound	Not determined.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	In use may form flammable/explosive vapour-air mixture.
------------------------------------	---

10.4. Conditions to avoid

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Oxidising materials.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Flammable/combustible materials.
--------------------	----------------------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Oxides of carbon.
----------------------------------	-------------------

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	No data recorded.
Acute toxicity - oral	
Notes (oral LD ₅₀)	No specific test data are available.
Acute toxicity - dermal	
Notes (dermal LD ₅₀)	No specific test data are available.

STYCCOBOND F60

Acute toxicity - inhalation

Notes (inhalation LC₅₀) No specific test data are available.

Skin corrosion/irritation

Skin corrosion/irritation Irritating to skin.

Animal data No specific test data are available.

Human skin model test No specific test data are available.

Extreme pH No specific test data are available.

Serious eye damage/irritation

Serious eye damage/irritation Irritation of eyes is assumed.

Respiratory sensitisation

Respiratory sensitisation No specific test data are available.

Skin sensitisation

Skin sensitisation Sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro No specific test data are available.

Genotoxicity - in vivo No specific test data are available.

Carcinogenicity

Carcinogenicity No specific test data are available.

IARC carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity - fertility No specific test data are available.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Target organs Respiratory system, lungs Skin

Aspiration hazard

Aspiration hazard Not relevant.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting.

Ingestion

Irritating. Symptoms following overexposure may include the following: Nausea, vomiting. Stomach pain.

Skin contact

Product has a defatting effect on skin. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.

Eye contact

Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. A single exposure may cause the following adverse effects: Corneal damage.

STYCCOBOND F60

Acute and chronic health hazards	Contains a substance with possible risk of harm to the unborn child. May cause damage to organs through prolonged or repeated exposure.
Route of entry	Inhalation Skin and/or eye contact
Target organs	Eyes Respiratory system, lungs Skin
Medical symptoms	Difficulty in breathing. Dryness and/or cracking. Intoxication. Irritation of eyes and mucous membranes. Nausea, vomiting.
Medical considerations	Chronic respiratory and obstructive airway diseases. Skin disorders and allergies. Pre-existing eye problems.

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment.

12.1. Toxicity

Toxicity Toxic to aquatic life with long lasting effects.

Acute toxicity - fish Not determined

Acute toxicity - aquatic invertebrates Not determined.
Highly insoluble in water.

Acute toxicity - aquatic plants Not determined.
Highly insoluble in water.

Acute toxicity - microorganisms Not determined.
Highly insoluble in water.

Acute toxicity - terrestrial Not determined.
Highly insoluble in water.

Chronic toxicity - fish early life stage Not determined.

Short term toxicity - embryo and sac fry stages Not determined.

Chronic toxicity - aquatic invertebrates Not determined.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

Phototransformation Not determined.

Stability (hydrolysis) Highly insoluble in water.

Biodegradation Not readily biodegradable.

Biological oxygen demand No specific test data are available.

Chemical oxygen demand No specific test data are available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

12.4. Mobility in soil

STYCCOBOND F60

Mobility	The product is insoluble in water and will spread on the water surface. The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
Adsorption/desorption coefficient	Not determined.
Henry's law constant	Not determined.
Surface tension	Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	This substance is not classified as PBT or vPvB according to current EU criteria.
---	---

12.6. Other adverse effects

Other adverse effects	None known.
------------------------------	-------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods	Should be disposed of as hazardous waste via a licensed waste operator.
-------------------------	---

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1133
UN No. (IMDG)	1133
UN No. (ICAO)	1133
UN No. (ADN)	1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	ADHESIVES
---------------------------------------	-----------

Proper shipping name (IMDG)	ADHESIVES (CONTAINS NAPHTHA (PETROLEUM), HYDROTREATED LIGHT; LOW BOILING POINT HYDROGEN)
------------------------------------	--

Proper shipping name (ICAO)	ADHESIVES
------------------------------------	-----------

Proper shipping name (ADN)	ADHESIVES
-----------------------------------	-----------

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



STYCCOBOND F60

14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS	F-E, S-D
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	No listing known.
Guidance	Safety Data Sheets for Substances and Preparations.
Authorisations (Title VII Regulation 1907/2006)	No specific authorisations are known for this product.
Restrictions (Title VIII Regulation 1907/2006)	No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	F.Ball and Company Ltd Technical Datasheet.
Key literature references and sources for data	Health and Safety Executive Guidance Note EH40 (amended annually). Workplace Exposure Limits.
Revision comments	Section 9: update. Section 14 update
Revision date	16/08/2017
Revision	20

STYCCOBOND F60

Supersedes date	17/02/2016
SDS status	Approved.
Hazard statements in full	H224 Extremely flammable liquid and vapour. H225 Highly flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.