

# PRODUCT DATASHEET

March 2021



## Hardwood Plywood 'FGPP' FSC® Certified Hardwood Plywood

|                        |                              |
|------------------------|------------------------------|
| Length                 | 2440mm                       |
| Width                  | 1220mm                       |
| Thickness              | 6.00mm                       |
| Average Density        | 540kg/m <sup>3</sup>         |
| Pieces per pack        | 150                          |
| Volume per pack        | 2.6790m <sup>3</sup>         |
| Service Class          | EN636-2                      |
| Glue Bond              | EN314-2 Class 3              |
| Formaldehyde Class     | E1                           |
| Country of Manufacture | China                        |
| Environmental Status   | FSC® Certified               |
| FSC® Product Type      | W8.1 (Plywood/Blockboard)    |
| Product Grade          | Pencil Cedar F/B             |
| Product Type           | Hardwood F/B Eucalyptus Core |

### Material Safety Data for Plywood and Wood Based Panels:

Wood-based panels can be bulky and heavy and this needs to be considered when manual handling is performed. Further information can be obtained from the HSE website. [www.hse.gov.uk/pubns/indg318](http://www.hse.gov.uk/pubns/indg318)

Machining and processing (cutting or sanding for example) of wood-based panels will produce dust which can cause irritation to eyes and throat. The use of protective goggles and face-masks and suitable dust extraction equipment is therefore recommended. Further information can be obtained from the HSE website. [www.hse.gov.uk/woodworking/wooddust](http://www.hse.gov.uk/woodworking/wooddust)

Wood splinters can cause irritation or infection if they enter the skin - wearing suitable gloves is therefore recommended to protect the hands.

Under certain circumstances the release of small quantities of formaldehyde gas from wood-based panels containing formaldehyde based adhesives can cause irritation of the eyes and throat. Always ensure adequate ventilation is available in areas where products are stored or processed.

All wood-based products are flammable - store them in a cool, dry and well ventilated place away from sources of heat, flames or sparks.

