

Plain Stripe

6 Colourways
4 Colourways

General usage and
light commercial carpet tile

General usage and light commercial carpet tile

- Suitable for general office and light commercial areas
 - Attractive encapsulated yarn
 - Available from stock
- Bleach resistant yarn
 - Easy to clean
 - Passes relevant flammability test
 - Cost-effective floorcovering solution

SPECIFICATION		PERFORMANCE TESTS	
	Style Tufted Loop Pile Tile 1/10" gauge		Anti-static < 2Kv body voltage. Suitable for use with computers
	Yarn Construction 100% Polypropylene		Static Load to BS 4939 Not less than 80% recovery after 24 hours
	Pile Yarn Weight 420 gsm		Colour Fastness to BS 1006: To Light BS EN (ISO105 – BO2) Better than 6
	Pile Height 3.5mm		To Shampoo BS 1006 - UK - TB Change in shade 4 - 5
	Pile Density 133,600 tufts per m²		To Rubbing BS EN (ISO105 - X12) Wet 4 - 5, Dry 4 - 5
	Total Weight 4200 gsm		Flammability Floorcoverings tested to BS4790 Low Radius
	Total Thickness 6.5mm		(Hot Metal Nut Test) of Char
	Backing Bitumen		Installation Method Stripe only to be laid tessellated
	Dimensions 50cm x 50cm		

INSTALLATION Sub floors should be clean, dry and flat and prepared in accordance with BS5325. Timber floors should be covered with plywood or other appropriate sheet materials. For tiles use F Ball tackifier F41. Tiles may be laid tessellated or broadloom. Tiles should be allowed to condition for a minimum of 24 hours at the expected temperature and humidity prevailing when the building is in use.

COLOUR For technical reasons, as with all textile materials, it may not be possible to colour match from different batches. Orders requiring colour match should be placed at the same time. Production may therefore show variations to the sample card.

MAINTENANCE It is recommended that a maintenance schedule be initiated from the date of installation to achieve maximum life expectancy of the product. Regular vacuum cleaning with a twin motored upright vacuum cleaner is essential. All spillages and stains should be attended to immediately. It is imperative that all internal carpets are well protected from outside soiling and moisture by the use of barrier matting such as Mat.Works.



**Beach Bros Ltd.**
Western Road, St Thomas, Exeter EX4 1EQ


Western Road, St Thomas, Exeter EX4 1EQ
T. 01392 421000 F. 01392 423525 E. orders@beachbros.co.uk
www.beachbros.co.uk

As distributed by:


**Beach Bros Ltd.**
Western Road, St Thomas, Exeter EX4 1EQ




**Beach Bros Ltd.**
Western Road, St Thomas, Exeter EX4 1EQ




Aegean




Paprika




Pewter




Quartz




Sapphire




Jet




Jet / Quartz



Aegean / Sapphire



Lime / Quartz



Quartz / Pewter