

STAUF MULTICONTACT KORK

Solvent-free Dispersion contact adhesive

Special features:

- ▶ excellent green and final tack
- ▶ very long contact tack
- ▶ easy to roll out
- ▶ very economical



Application range

- ▶ Cork floor coverings made of agglomerated cork according to DIN EN 12104
- ▶ Cork wall coverings

Suitable sub floors

- ▶ chipboards V100 (E1), OSB boards
- ▶ unlaminated gypsum fibre boards
- ▶ STAUF levelling compounds
- ▶ masonry
- ▶ concrete walls
- ▶ cement-bonded plaster
- ▶ gypsum cardboard-lay plate

Suitable levelling compounds

- ▶ STAUF SPP 95
- ▶ STAUF AS
- ▶ STAUF OS
- ▶ STAUF GS
- ▶ STAUF FZ
- ▶ STAUF RM
- ▶ STAUF GS-Stand
- ▶ STAUF SSP RAPID

Product properties

- ▶ suitable for sub floor heating systems
- ▶ solvent-free
- ▶ immediate fixation of floorings

Color

- ▶ white

Required quantities per m²

- ▶ 290 g

Open time

- ▶ approx. 2 hours at 20 °C

Flash time

- ▶ 20 - 90 min.

Accessibility

- ▶ immediately

Additional instructions

- ▶ On highly absorbent subsurfaces the absorbency should be regulated by using e.g. STAUF VDP-130 as a base.
- ▶ On cork the adhesive can be applied to the back of the covering up to 18 hours before glueing.
- ▶ Highly absorbent walls need priming first.
- ▶ Adhesive can be applied on the back of the floorcovering up to 18 hours before sticking down.

Room climate at work site

- ▶ minimum 15 °C, maximum 75% rel. humidity, preferably max. 65%

Transport requirements

- ▶ frost-free

Storage requirements

- ▶ frost-free

Shelf-life

- ▶ 6 months

Available packaging

- ▶ 5 kg plastic bucket

Giscode

- ▶ D1

Emicode

- ▶ EC1-R

DIBT

- ▶ Z-155.20-445

Sub floor preparation

It must be ensured that the sub floor is ready for installation by performing proper sub floor preparation, floors must be clean, have sufficient surface strength, must be level, permanently dry and free of cracks. A mechanical pretreatment of the subfloor (sweeping, vacuuming, mechanical brushing, sanding, milling, shot blasting) must be performed depending on type and condition of sub floor. Cracks and joints, except expansion joints and other construction joints, shall be solidly closed with STAUF casting resin and floor brackets. Cavities and indentations can be filled with a non self-levelling STAUF levelling compound. Before installing floor coverings, the properly prepared sub floors must normally be levelled using the appropriate STAUF levelling compound. Once sub floors have been levelled, do not apply primers.

Processing

With regard to installation, always observe manufacturer's instructions. It is recommended to store cork tiles and adhesive in installation room before starting work. Only take cork tiles out of packing immediately before installation. Apply adhesive liberally and evenly with the appropriate roller on sub floor and backing of the floor covering. Let adhesive dry until both adhesive layers become transparent. Install floor covering during laying time and rub or press down firmly. (the higher the pressure the stronger the bond). Tap down edges using rubber hammer. Position can not be corrected after laying. After adhesive has been applied to backing, cork tiles can be stored for 18 h.

Accessibility

Immediately after installation. Surface treatment of cork floor tiles at the earliest after 16 hours.

Limitation of liability

The foregoing representations are based on the results of our most current product and material testing and are of a non-obligatory advisory nature only since we have no control over the actual quality of workmanship, materials used and worksite conditions. As such, they do not constitute an express or implied warranty of any kind. The same applies to our commercial and technical consultation services which are provided free-of-charge and without obligation. Therefore, we strongly recommend that prior on-site testing be conducted to observe and study the suitability of the product for the intended purpose. With the release of this technical information, all prior technical information (technical data sheets, installation recommendations and other information regarding similar purposes) becomes invalid.