

Worktop Oil

Technisches Merkblatt
September 2019
Seite 1/2



- » *with natural oils*
- » *suitable for all kinds of wooden worktops*

The benefits of the product:

SAICOS Worktop Oil is a special type of oil developed according to the latest research to provide a durable, hardwearing natural surface with a quick drying time – normally between 4-5 hours. Penetrating deep into the wood, SAICOS Worktop Oil protects from the inside, retaining the wood's elasticity, whilst natural waxes protect the surface and ensure high durability. SAICOS Worktop Oil connects permanently to the wood, so no sanding is necessary during renovation with the exception of strongly greyed or heavily worn worktops.

Extremely fast drying:

Matt 4-5 hours = 2 coats on the same day!

Preparation:

Wood surface must be dry and clean (max. moisture content 12 %). Any paints and varnishes must be removed (final sanding grain 120-150). Remove dust thoroughly. Previously oil- or wax-treated surfaces do not require sanding (cleaning with *Ecoline Magic Cleaner*) except wood which is strongly greyed or worn.

Processing:

Apply with SAICOS Oil/Wax-Roller, SAICOS Floor Brush or SAICOS Flat Brush. SAICOS Worktop Oil is ready to use. Stir well – do not thin.

Note: Do not pour SAICOS Worktop Oil directly on the surface, rather work with a Paint Tray

Colour:

3355 Matt Colourless

3356 Pure

Application:

SAICOS Flat Brush or SAICOS Oil/Wax-Roller: Stir the oil well (do not shake) and pour into a paint tray. Apply a thin and even coat of oil avoiding over application and puddling. Leave to dry for a minimum for 5 hours before applying a second coat if required.

Lint Free Cloth:

Stir the oil well (do not shake) and pour into a paint kettle or similar. Apply a thin and even coat of oil and leave to penetrate for 5 minutes. Using a clean lint free cloth remove all of the oil leaving the worktop almost completely dry. Repeat if required.

Maintenance:

Worktops finished with SAICOS Worktop Oil can be cleaned using SAICOS Worktop Cleaner as regularly as required. Annually,

worktops should be refinished with a thin coat of SAICOS Worktop Oil to ensure optimum durability.

Storability:

At least 5 years in sealed container. The liquid product is not susceptible to frost. To restore good spreadability after exposure to frost, store at room temperature for several hours and stir well.

Ingredients:

Alkyds based on natural, vegetable oils, additives, pigments, solvents

Safety notes – first aid:

Keep out of the reach of children. Do not fill into containers normally used for food and drink. Wash out any product-soaked rags immediately or store in an airtight container (danger of combustion). The dried coating is normally inflammable acc. to EURO norm EN 13501 (DIN 4102 B2).

Contains: 2-butanone oxime, Phthalic anhydride. May produce an allergic reaction. Safety data sheet available on request.

EU limit for one component coatings (cat. A/i): 500 g/l (2010).

SAICOS Worktop Oil contains max. 500 g/l VOC.

For more information, please read our current technical data sheets.

SAICOS COLOUR GmbH

Carl-Zeiss-Str. 3

D-48336 Sassenberg

☎ +49 2583 3037-0

☎ +49 2583 3037-10

✉ info@saicos.de

www.saicos.de