

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
 Date of issue: 10/01/2019 Revision date: 20/12/2018 Supersedes: 25/10/2018 Version: 3.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Trade name : ColourSeal Premium Colour Floor Sealant

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

BL FLOORING SUPPLIES
 Unit 5a, Gatton Road
 St Werburghs
 BS2 9SH Bristol
 T 0117 955 54 54 - F 0117 955 26 26
info@blflooring.co.uk - www.blflooring.co.uk

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number	Comment
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	+44 20 7188 7188	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine, Methyl tris-(methyl ethyl ketoximo) silane, Tetrakis(methylethylketoximino)silane, 3-aminopropyltriethoxysilane, 3-(2-aminoethylamino)propyltrimethoxysilane. May produce an allergic reaction.
 EUH210 - Safety data sheet available on request.

2.3. Other hazards

Contains PBT/vPvB substances >= 0.1% assessed in accordance with REACH Annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C18-C24, n-alkanes, isoalkanes, cyclics, <2% aromatics	(CAS-No.) 1437280-85-7 (EC-No.) 940-734-7 (REACH-no) 01-2120078782-46	10 - 25	Asp. Tox. 1, H304
Methyl tris-(methyl ethyl ketoximo) silane	(CAS-No.) 22984-54-9 (EC-No.) 245-366-4 (REACH-no) 01-2119987100-43	1 - 5	Eye Irrit. 2, H319 Skin Sens. 1, H317 STOT RE 2, H373
Dodecamethylcyclohexasiloxaan substance listed as REACH Candidate (Dodecamethylcyclohexasiloxane (D6)) PBT substance vPvB substance	(CAS-No.) 540-97-6 (EC-No.) 208-762-8	0,1 - 1	Not classified

ColourSeal Premium Colour Floor Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
Methyl tris-(methyl ethyl ketoximo) silane	(CAS-No.) 22984-54-9 (EC-No.) 245-366-4 (REACH-no) 01-2119987100-43	(3,755 =<C < 100) Skin Sens. 1, H317

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove victim to fresh air.
First-aid measures after skin contact	: After contact with skin, wash immediately and thoroughly with water and soap.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Seek medical attention if ill effect or irritation develops.
First-aid measures after ingestion	: Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Not expected to present a significant skin hazard under anticipated conditions of normal use.
Symptoms/effects after eye contact	: Direct contact with the eyes is likely slightly irritating.
Symptoms/effects after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : All extinguishing media allowed.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Precautionary measures fire	: Exercise caution when fighting any chemical fire. Evacuate unnecessary personnel. Do not breathe fumes from fires or vapours from decomposition.
Firefighting instructions	: Cool down the containers exposed to heat with a water spray.
Protection during firefighting	: Wear a self contained breathing apparatus.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : [In case of inadequate ventilation] wear respiratory protection. Equip cleanup crew with proper protection.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

No additional information available

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling temperature	: 5 - 40 °C
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in dry, well-ventilated area.
Maximum storage period	: 12 months

ColourSeal Premium Colour Floor Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Storage temperature : 5 - 25 °C

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Time of penetration is to be checked with the glove producer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)		> 0,1		EN ISO 374

Eye protection:

Type	Use	Characteristics	Standard
Safety glasses	Droplet	With side shields	EN 166

Skin and body protection:

No special clothing/skin protection equipment is recommended under normal conditions of use

Respiratory protection:

No special respiratory protection equipment is recommended under normal conditions of use with adequate ventilation

Device	Filter type	Condition	Standard
Gas mask	ABEK	If conc. in air > exposure limit, Long term exposure	

Personal protective equipment symbol(s):



Consumer exposure controls:

Avoid contact with skin and eyes. Take off immediately all contaminated clothing. Wash hands and other exposed areas with soap and water before leaving work.

Other information:

Do not eat, drink or smoke during use. Wash contaminated clothing before reuse.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste.
Colour	: According to product specification.
Odour	: characteristic.
Density	: 1,39 g/ml
Solubility	: Water: Negligible.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal use.

ColourSeal Premium Colour Floor Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

None under normal use.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Methyl tris-(methyl ethyl ketoximo) silane (22984-54-9)

LD50 oral rat	2463 mg/kg (OECD 401 method)
LD50 dermal rat	> 2000 mg/kg (OECD 402 method)

Dodecamethylcyclhexasiloxaan (540-97-6)

LD50 oral rat	2000 mg/kg
LD50 dermal rat	2000 mg/kg

Hydrocarbons, C18-C24, n-alkanes, isoalkanes, cyclics, <2% aromatics (1437280-85-7)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified

Methyl tris-(methyl ethyl ketoximo) silane (22984-54-9)

NOAEL (animal/male, F0/P)	>= 250 mg/kg (OECD 422 method)
NOAEL (animal/female, F0/P)	>= 250 mg/kg (OECD 422 method)

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Methyl tris-(methyl ethyl ketoximo) silane (22984-54-9)

LOAEL (oral, rat, 90 days)	50 mg/kg bodyweight/day
NOAEL (subacute, oral, animal/male, 28 days)	10 mg/kg bodyweight (OECD 422 method)

Dodecamethylcyclhexasiloxaan (540-97-6)

LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight/day
LOAEC (inhalation, rat, gas, 90 days)	10 ppmv/6h/day

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

Methyl tris-(methyl ethyl ketoximo) silane (22984-54-9)

LC50 fish 1	> 120 mg/l Oncorhynchus mykiss (Rainbow trout)
LC50 fish 2	972,34 mg/l (OECD 203 method)

ColourSeal Premium Colour Floor Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EC50 Daphnia 1	231,84 mg/l (OECD 202 method)
EC50 72h algae (1)	18,45 mg/l (OECD 201 method)
ErC50 (algae)	72h 94 mg/l Pseudokirchneriella subcapitata
NOEC (acute)	57,67 mg/l (OECD 204 method)
NOEC (chronic)	>= 115,34 mg/l (OECD 211 method)
NOEC chronic fish	57,67 mg/l

Dodecamethylcyclhexasiloxaan (540-97-6)

EC50 other aquatic organisms 1	> 420 mg/l
EC50 72h algae (1)	0,002 mg/l OECD 201
NOEC chronic fish	4,4 µg/l Pimephales promelas
NOEC chronic crustacea	0,0046 mg/l
NOEC chronic algae	>= 0,002 mg/l

Hydrocarbons, C18-C24, n-alkanes, isoalkanes, cyclics, <2% aromatics (1437280-85-7)

LC50 fish 1	> 100 mg/l
EC50 Daphnia 1	> 100 mg/l
EC50 72h algae (1)	> 100 mg/l

12.2. Persistence and degradability

Methyl tris-(methyl ethyl ketoximo) silane (22984-54-9)

Biodegradation	28d 0 % (OECD 301A method)
----------------	----------------------------

Dodecamethylcyclhexasiloxaan (540-97-6)

Persistence and degradability	Not readily biodegradable.
Biodegradation	4,5 % (OECD 310 method)

12.3. Bioaccumulative potential

Methyl tris-(methyl ethyl ketoximo) silane (22984-54-9)

Log Pow	9,83
---------	------

Dodecamethylcyclhexasiloxaan (540-97-6)

Log Pow	8,87
Log Kow	8

Hydrocarbons, C18-C24, n-alkanes, isoalkanes, cyclics, <2% aromatics (1437280-85-7)

Log Pow	> 7,2
---------	-------

12.4. Mobility in soil

Methyl tris-(methyl ethyl ketoximo) silane (22984-54-9)

Log Koc	5,481 EPA (Environmental Protection Agency)
---------	---

12.5. Results of PBT and vPvB assessment

Component

Methyl tris-(methyl ethyl ketoximo) silane (22984-54-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Dodecamethylcyclhexasiloxaan (540-97-6)	This substance/mixture meets the PBT criteria of REACH regulation, annex XIII This substance/mixture meets the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

ColourSeal Premium Colour Floor Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances 08 04 10 - waste adhesives and sealants other than those mentioned in 08 04 09

SECTION 14: Transport information

In accordance with ADR

ADR

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

No supplementary information available

14.6. Special precautions for user

Overland transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Methyl tris-(methyl ethyl ketoximo) silane - Hydrocarbons, C18-C24, n-alkanes, isoalkanes, cyclics, <2% aromatics
3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Methyl tris-(methyl ethyl ketoximo) silane

Contains a substance on the REACH candidate list in concentration 0.1% or with a lower specific limit: Dodecamethylcyclohexasiloxane (D6) (EC 208-762-8, CAS 540-97-6)

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Substance(s) are not subject to Regulation (EC) No 850/2004 of the European Parliament and of the Council of 29 April 2004 on persistent organic pollutants and amending Directive 79/117/EEC.

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

ColourSeal Premium Colour Floor Sealant

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 16: Other information

Full text of H- and EUH-statements:	
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
EUH208	Contains N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine, Methyl tris-(methyl ethyl ketoximo) silane, Tetrakis(methylethylketoximino)silane, 3-aminopropyltriethoxysilane, 3-(2-aminoethylamino)propyltrimethoxysilane. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product