

Lightweight

PRODUCT DATA SHEET



Poplar/Ilomba construction giving significant weight saving and very high quality faces.

Our **+** Hanson Lightweight Plywood offers stability, ease of cutting and machining and most importantly low density.

+ Hanson Lightweight Plywood is available in a number of thicknesses as either Poplar throughout or as an exotic Ilomba faced, Poplar core combi-product. Poplar throughout offers the user a light weight, light colour, high homogeneity with a barely perceptible grain. Whereas the pinker hue of the Ilomba face offers versatility and ideal support for decorative coating materials.

Applications

Interior use - general joinery, shop/bar fitting, laminating, veneering, furniture, motorhomes, caravans, portable buildings.

SPECIFICATION DETAIL:

Thicknesses (mm)	3mm-25mm (Poplar) ; 3mm -15mm (Ilomba)
Dimensions (mm)	2440 x 1220/2500 x 1220/ 3050 x 1220
Average density	400 Kg/m ³ ± 10%
Product standard	EN 636-1
Glue bond	EN 314-2 Class 1 (Interior)
Formaldehyde release	Class E1 (tested to EN 717-2)
Moisture content	8%-13%
Veneers	High quality face and core
Environmental certification	PEFC™ 100%
European Timber Regulation (EUTR) status	Compliant - sourced within EU
CE marked	BS EN 13986
Material safety data sheet	Available

CONTACT:

Drakes Industrial Estate
Shay Lane, Halifax
West Yorkshire
HX3 6RL

Tel: 01422 330444
Fax: 01422 330706
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk



For more information visit:
www.hanson-plywood.co.uk

June 2020