



Hanson Plywood Ltd are birch specialists who stock a large and comprehensive range of Birch Plywood

†† Birch Plywood is suitable for use in both interior and exterior applications.

With a selection of grading options on surface quality and array of thicknesses and sheet sizes, the product range allows a defined route to your specific requirements.

Birch veneers are bonded with an exterior, phenol-formaldehyde glue, allowing panels to be used in most humid environments and, if fully sealed, in many exterior uses.

The above qualities allow †† Birch Plywood to be used in an extensive and varied range of applications.

Applications

Wall Linings, Flooring, General Joinery, Shopfitting, Construction, Furniture, Packaging.

SPECIFICATION DETAIL:

Thicknesses(mm)	4	6	6.5	8	9	12	15	18	21	24	27	30	35	50
Number of Plies	3	5	5	6/7	7	9	11	13	15	17	19	21	25	36
Dimensions (mm)	2440 x 1220, 1220 x 2440, 1220 x 3050, 1525 x 1525, 1525 x 3050													
Average density	Approx. 700 kg/m ³													
Product standard	EN 636-2													
Glue bond	EN 314-2 Class 3 (Exterior)													
Formaldehyde release	Class E1 (Tested to EN 717-2) - CARB Phase 2 compliant (On Request)													
Moisture content	8%-10% at manufacture													
Grading	B/BB, S+/BB, BB, BB/CP, CP, C													
Core	Uniform and consistent core construction													
Environmental certification	FSC® & PEFC™ subject to availability													
European Timber Regulation (EUTR) status:	Compliant													
CE marked	BS EN 13986													
Material safety data sheet	Available													

CONTACT:

Drakes Industrial Estate
Shay Lane, Halifax
West Yorkshire
HX3 6RL

Tel: 01422 330444
Fax: 01422 330706
Email: sales@hanson-plywood.co.uk
www.hanson-plywood.co.uk



For more information visit:
www.hanson-plywood.co.uk